



Motorenöle

Motor oils

Getriebeöle

Gear oils

Zweitaktöle und
Traktorenöle

Two-stroke oils and
tractor oils

Hydrauliköle

Hydraulic oils

Industrie- und
Spezialschmierstoffe

Industrial and
specialty lubricants

PENNASOL MULTIGRADE SUPER HD SAE 20W-50

PENNASOL MULTIGRADE SUPER HD SAE 20W-50 is a multigrade motor oil, which meets the requirements of modern spark-ignition petrol or diesel engines. The adjustable viscosity guarantees good lubrication under all operating conditions. According to some manufacturers' recommendations this oil can be used throughout the year.

ACEA-/API-specifications:

API SF (obsolete)

API CD (obsolete)

Typical characteristics PENNASOL MULTIGRADE SUPER HD SAE 20W-50:

(The given data are typical data. Please observe operating prescriptions.)

Parameter	Method	Unit	
SAE class	SAE J 300	g/cm ³	SAE 20W-50
Density 15 °C	DIN EN ISO 12185		0.876 – 0.886
Kin. viscosity @ 40 °C	DIN 51562 -1	mm ² /s	160
Kin. viscosity @ 100 °C	DIN 51562-1	mm ² /s	18.2
Viscosity index	DIN ISO 2909		min. 120
Total Base Number	DIN ISO 3771	mg KOH/g	5.3 – 6.3
Dyn. viscosity @ -15°C	DIN 51377	mPa*s	max. 9,500
Flash point COC	DIN ISO 2592	°C	min. 220
Pour Point	DIN ISO 3016	°C	max. -27



Motorenöle <i>Motor oils</i>	Getriebeöle <i>Gear oils</i>	Zweitaktöle und Traktorenöle <i>Two-stroke oils and tractor oils</i>	Hydrauliköle <i>Hydraulic oils</i>	Industrie- und Spezialschmierstoffe <i>Industrial and specialty lubricants</i>
--	--	--	--	--

Available Packaging:

	Bulk	965 Liter	208 Liter	60 Liter	20 Liter	4*5 Liter	4*4 Liter	12*1 Liter
<i>PENNASOL MULTIGRADE SUPER HD SAE 20W-50</i>	•	•	•	•	•	•		•

¹Version 7 – 07/2018

¹ This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AVISTA OIL or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale.