

Motorenöle

Motor oils

Getriebeöle

Gear oils

**Zweitaktöle und
Traktorenöle**

*Two-stroke oils and
tractor oils*

Hydrauliköle

Hydraulic oils

**Industrie- und
Spezialschmierstoffe**

*Industrial and
specialty lubricants*

PENNASOL COMPRESSOR OIL VDL

PENNASOL COMPRESSOR OIL VDL is based on paraffinic base oil and modern additive technology. Effective zinc and ash free components guarantee optimal lubrication and long term protection against oxidation. To minimize wear it guarantees sufficient lubrication at high operating temperatures as well as low temperatures. Selected additives minimize carbon residue formation which might otherwise lead to ignition. The product is characterized by good viscosity-temperature behavior and reliable corrosion protection.

PENNASOL COMPRESSOR OIL VDL can be used for the circulatory lubrication of jet engines where the manufacturer does not prescribe HD engine oils.

Specification:

- DIN 51506
- FZG-Test A8,3/90 Schadenskraftstufe: 13

Recommendations:

Low coking tendencies	VBL / VCL (exceeded)
-----------------------	----------------------

Parameter	Unit	Testing method	PENNASOL COMPRESSOR OIL VDL		
			ISO VG 46	ISO VG 68	ISO VG 100
Density 15°C	kg/m ³	DIN EN ISO 12185	864	871	878
Flash point COC	°C	DIN ISO 2592	230	230	240
Pour point	°C	DIN ISO 3016	-24	-24	-21
Viscosity 40°C	mm ² /s	DIN 51562-1	44,8	66,5	98,7
Viscosity 100°C	mm ² /s	DIN 51562-1	6,8	9,0	11,5
VI		DIN ISO 2909	113	109	102

12/2017

Version 4

1

¹ This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AVISTA OIL Group or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale.