

Motorenöle

Motor oils

Getriebeöle

Gear oils

Zweitaktöle und Traktorenöle

Two-stroke oils and tractor oils

Hydrauliköle

Hydraulic oils

Industrie- und Spezialschmierstoffe

Industrial and specialty lubricants

PENNASOL INDUSTRIAL GEAR OIL CLP

PENNASOL INDUSTRIAL GEAR OIL CLP is based on paraffinic base oil and modern additive technology. Effective zinc and ash free components guarantee optimal lubrication and long term protection against oxidation. It is used to lubricate spur-, bevel- and worm gears, gear trains and bearings with dip and circulator lubrication, jaw clutches axial bearings of roller mill stands and highly loaded sliding surfaces (joints). The oil performs very well in gears and bearings of rolling mill stands, on calenders, mining machinery, winches and crushing mills.

Specification:

- DIN 51517 part 3
- FZG-Test A8,3/90 load stage: >12
- FE8 wear test (DIN 51819-3): bearing wear 1,1mg; cage wear 127mg

Recommendations:

AIST 224 (US Steel)	AGMA 9005 E02 (EP)
---------------------	--------------------

Parameter	Unit	Testing method	PENNASOL INDUSTRIAL GEAR OIL CLP		
			ISO VG 68	ISO VG 100	ISO VG 150
Density 15°C	kg/m ³	DIN EN ISO 12185	872	879	885
Flash point COC	°C	DIN ISO 2592	230	240	240
Pour point	°C	DIN ISO 3016	-27	-24	-24
Viscosity 40°C	mm ² /s	DIN 51562-1	66,7	92,6	150,7
Viscosity 100°C	mm ² /s	DIN 51562-1	9,0	11,5	15,1
VI		DIN ISO 2909	109	102	101

12/2017

Version 5

1

¹ This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AVISTA OIL Group or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale.