

Motorenöle

Motor oils

Getriebeöle

Gear oils

**Zweitaktöle und
Traktorenöle**

*Two-stroke oils and
tractor oils*

Hydrauliköle

Hydraulic oils

**Industrie- und
Spezialschmierstoffe**

*Industrial and
specialty lubricants*

PENNASOL INDUSTRIAL SLIDE WAY OIL CGLP

PENNASOL INDUSTRIAL SLIDE WAY OIL CGLP is based on paraffinic base oil and modern additive technology. Effective zinc and ash free components guarantee optimal lubrication and long term protection against oxidation. It is characterized by good sliding properties as well as high tackiness. It contains corrosion inhibitors to prevent rust formation and stains on slide ways and track surfaces. It is compatible with most of drilling-, cutting or grinding emulsions. The lubricant film of the slide way oil is not washed off.

PENNASOL CGLP can be used for all types of lubrication systems such as pressure, circulating or central lubrication. If necessary it can be applied manually. It can also be used for lubricating bearings and gear boxes

Specification:

- DIN 51502

Recommendations:

Very good stick-slip characteristics	High tackiness
Good demulsification	

Parameter	Unit	Testing method	PENNASOL INDUSTRIAL SLIDE WAY OIL CGLP		
				ISO VG 320	
Density 15°C	kg/m ³	DIN EN ISO 12185		895	
Flash point COC	°C	DIN ISO 2592		240	
Pour point	°C	DIN ISO 3016		-9	
Viscosity 40°C	mm ² /s	DIN 51562-1		314,8	
Viscosity 100°C	mm ² /s	DIN 51562-1		25,0	
VI		DIN ISO 2909		100	

12/2017

Version 4

1

¹ This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AVISTA OIL Group or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale.