

Motorenöle

Motor oils

Getriebeöle

Gear oils

**Zweitaktöle und
Traktorenöle**

*Two-stroke oils and
tractor oils*

Hydrauliköle

Hydraulic oils

**Industrie- und
Spezialschmierstoffe**

*Industrial and
specialty lubricants*

PENNASOL SPEZIAL HAFTÖL

PENNASOL SPEZIAL HAFTÖL is based on paraffinic base oil and modern additive technology. It is a lubricating oil, which is very ropy and adhesive and provides stable, pressure-resistant lubricant films. It possesses a very pronounced adhesive capacity so that the oil film is maintained on vertical surfaces. Therefore vertical guides and slide ways can be lubricated because the lubricating film will not tear. It is suitable for slide and guide ways on all types of machinery and prevents stick slip motion even at very low speeds. Effective zinc and ash free components guarantee optimal lubrication and long term protection against oxidation.

Specification:

Recommendations:

Very good stick-slip characteristics	High tackiness
Good demulsification	Less oil usage
Longer maintenance interval	Better lubricity

Parameter	Unit	Testing method	PENNASOL SPEZIAL HAFTÖL		
			ISO VG 68	ISO VG 100	ISO VG 150
Density 15°C	kg/m ³	DIN EN ISO 12185	872	877	883
Flash point COC	°C	DIN ISO 2592	220	230	240
Pour point	°C	DIN ISO 3016	-12	-12	-12
Viscosity 40°C	mm ² /s	DIN 51562-1	64,1	96,5	141,8
Viscosity 100°C	mm ² /s	DIN 51562-1	9,0	11,6	15,2
VI		DIN ISO 2909	107	102	102

12/2017

Version 4

1

¹ This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AVISTA OIL Group or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale.