



**Motorenöle**

*Motor oils*

**Getriebeöle**

*Gear oils*

**Zweitaktöle und  
Traktorenöle**

*Two-stroke oils and  
tractor oils*

**Hydrauliköle**

*Hydraulic oils*

**Industrie- und  
Spezialschmierstoffe**

*Industrial and  
specialty lubricants*

## PENNASOL SUPERIOR SN SAE 10W-40

**PENNASOL SUPERIOR SN SAE 10W-40** is a high performance engine oil, which can be used a year-round. The latest additive technology is used to meet or in some cases exceed the requirements of the latest API specification API SN for petrol engines. The product is based on high quality base oils of API base oil categories II and III.

**PENNASOL SUPERIOR SN SAE 10W-40** offers optimum protection for current and previous car engines models and has increased fuel savings as compared to API SM oils. In the areas of wear, deposits and piston cleanliness the requirements of the API SN specification are even exceeded. API SN is backward compatible and can be used, where SL and SM is required.

### **ACEA-/API-specifications:**

ACEA A3/B4

API SN

API CF (obsolete)

### **OEM-approvals:**

MB-Approval 229.3

VW 502 00 / 505 00

### **Meets/suitable for use:**

Renault RN 0700 / RN 0710

JASO MA2 (level)



Original MB-approval  
BEAM / BEVO

**Motorenöle**

*Motor oils*

**Getriebeöle**

*Gear oils*

**Zweitaktöle und  
Traktorenöle**

*Two-stroke oils and  
tractor oils*

**Hydrauliköle**

*Hydraulic oils*

**Industrie- und  
Spezialschmierstoffe**

*Industrial and  
specialty lubricants*

			<b>PENNASOL SUPERIOR SN</b>
Parameter	Unit	Testing method	<b>SAE 10W-40</b>
Density 15°C	kg/m <sup>3</sup>	DIN EN ISO 12185	866
Flash point COC	°C	DIN ISO 2592	min. 200
Pour point	°C	DIN ISO 3016	-39
Viscosity 40°C	mm <sup>2</sup> /s	DIN 51562-1	94.5
Viscosity 100°C	mm <sup>2</sup> /s	DIN 51562-1	14.2
VI		DIN ISO 2909	155

01/2017

Version 5

The given data are typical data. Please observe operating prescriptions.

### Available packaging:

	Bulk	965 Liter	208 Liter	60 Liter	20 Liter	4 * 5 Liter	4 * 4 Liter	12 * 1 Liter	Notes:
PENNASOL SUPERIOR SN SAE 10W-40	•	•	•	•	•	•	•	•	

1

<sup>1</sup> This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AVISTA OIL Group or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale.