

Motorenöle
Motor oils
Getriebeöle
Gear oils
**Zweitaktöle und
Traktorenöle**
*Two-stroke oils and
tractor oils*
Hydrauliköle
Hydraulic oils
**Industrie- und
Spezialschmierstoffe**
*Industrial and
specialty lubricants*

PENNASOL HEAVY CUT 22, 32, 46 (metalworking oil non water miscible)

PENNASOL HEAVY CUT 22, 32, 46 are cutting oils for the application on steel and stainless steel. Because of their high lubricity PENNASOL HEAVY CUT 22, 32, 46 are well suited for tooth flank grinding and heavy cutting processes up to easy broaching operations. The base oil with low volatility and high viscosity index secures very good product stability and long-term process reliability

Application:

alloyed steel	unalloyed steel	aluminium	yellow metals
XX	XXX	X	X

XXX: excellent suitable

XX: very well suitable

X: suitable

-: not recommended

Active Components:

Ester	S (active)	S (not active)	P
X	X	XX	X

XX: high level

X: normal level

-: not contained

Technical Data:

value	unit	method	HEAVY CUT 22	HEAVY CUT 32	HEAVY CUT 46
viscosity 40°C	mm ² /s	DIN 51562-1	23,4	32,2	42,9
density 15°C	kg/m ³	DIN EN ISO 12185	866	870	871
flash point	°C	DIN ISO 2592	214	228	208
copper corr.	Grad	ASTM D 130	4b	4b	4b

09/2015

Version 3

¹ This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AVISTA OIL Group or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale.