



Motorenöle

Motor oils

Getriebeöle

Gear oils

**Zweitaktöle und
Traktorenöle**

*Two-stroke oils and
tractor oils*

Hydrauliköle

Hydraulic oils

**Industrie- und
Spezialschmierstoffe**

*Industrial and
specialty lubricants*

PENNASOL SUPER FLUID ATF ASIA

PENNASOL SUPER FLUID ATF ASIA is a premium-ATF-oil based on best additives and base oils of HC synthesis technology. This ATF oil is specially designed for the requirements of automatic transmissions of Asian origin in passenger cars and light commercial vehicles.

PENNASOL SUPER FLUID ATF ASIA is characterized by excellent flow properties at low temperatures and ensures smooth transmission operations.

Meets/suitable for use:

(Meets requirements for product approval, but there is no specific product approval notified)

Toyota Typ T, T-II, T-III, T-IV, Typ D-2

JASO M 315 Type 1A

Nissan Matic Fluid C, D, J

Mitsubishi SP-II, SP-III

Daihatsu Alumix ATF Multi

Suzuki ATF Oil, ATF Oil Special

Mazda ATF D-III, ATF M-3

Subaru ATF

Isuzu Besco ATF-II, ATF-III,

Hyundai,

Kia

DEXRON® III-H,II-D

GM Motors Type A Suffix A (TASA)

MERCON®

Allison C-4 (level)

Suitable for use:

Toyota ATF WS

Motorenöle

Motor oils

Getriebeöle

Gear oils

**Zweitaktöle und
Traktorenöle**

*Two-stroke oils and
tractor oils*

Hydrauliköle

Hydraulic oils

**Industrie- und
Spezialschmierstoffe**

*Industrial and
specialty lubricants*

			MOTOR GOLD Fluitec ATF ASIA
Parameter	Unit	Testing method	
Density 15°C	kg/m ³	DIN EN ISO 12185	846
Flash point COC	°C	DIN ISO 2592	min. 210
Pour point	°C	DIN ISO 3016	≤ -45
Viscosity 40°C	mm ² /s	DIN 51562-1	36.7
Viscosity 100°C	mm ² /s	DIN 51562-1	7.3
VI		DIN ISO 2909	169

06/2015

Version 3

The given data are typical data. Please observe operating prescriptions.

Available packaging:

	Bulk	965 Liter	208 Liter	60 Liter	20 Liter	4 * 5 Liter	12 * 1 Liter	Notes:
MOTOR GOLD Fluitec ATF ASIA	•	•	•	•	•		•	

1

¹ This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AVISTA OIL Group or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale.