



Motorenöle

Motor oils

Getriebeöle

Gear oils

**Zweitaktöle und
Traktorenöle**

*Two-stroke oils and
tractor oils*

Hydrauliköle

Hydraulic oils

**Industrie- und
Spezialschmierstoffe**

*Industrial and
specialty lubricants*

PENNASOL HIGHTEC 0W-40

PENNASOL HIGHTEC SAE 0W-40 is a high performance low-friction oil for modern petrol and diesel engines in passenger cars and small commercial vehicles. It is especially recommended for engines with turbocharger and multivalve technology. **PENNASOL HIGHTEC SAE 0W-40** is an oil to be used all the year round and especially suitable for oil-contaminating city and motorway driving.

Other advantages:

- Multifunctional use in petrol and diesel engines from different manufacturers
- Excellent oxidation stability using fully synthetic PAO base oils
- High fuel efficiency (fuel economy)
- Extrem high wear protection
- Lubricating film stability even at high operating temperatures
- Excellent cold starting properties

ACEA/API-specifications:

ACEA A3/B4

API SN

Meets/suitable for use:

(Meets requirements for product approval, but there is no specific product approval notified)

BMW Longlife-01

Ford WSS-M2C937-A

MB 229.5

MB 229.3

Porsche A40

Renault RN 0700/0710

VW 502 00/505 00

Motorenöle

Motor oils

Getriebeöle

Gear oils

**Zweitaktöle und
Traktorenöle**

*Two-stroke oils and
tractor oils*

Hydrauliköle

Hydraulic oils

**Industrie- und
Spezialschmierstoffe**

*Industrial and
specialty lubricants*

			PENNASOL HIGHTEC
Parameter	Unit	Testing method	SAE 0W-40
Density 15°C	kg/m ³	DIN EN ISO 12185	845
Flash point COC	°C	DIN ISO 2592	min. 210
Pour point	°C	DIN ISO 3016	-51
Viscosity 40°C	mm ² /s	DIN 51562-1	77.2
Viscosity 100°C	mm ² /s	DIN 51562-1	13.5
VI		DIN ISO 2909	180

01/2017

Version 4

The given data are typical data. Please observe operating prescriptions.

Available packaging:

	Bulk	965 Liter	208 Liter	60 Liter	20 Liter	4 * 5 Liter	12 * 1 Liter	Notes:
PENNASOL HIGHTEC SAE 0W-40	•	•	•	•	•	•	•	

1

¹ This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AVISTA OIL Group or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale.