



Motorenöle

Motor oils

Getriebeöle

Gear oils

**Zweitaktöle und
Traktorenöle**

*Two-stroke oils and
tractor oils*

Hydrauliköle

Hydraulic oils

**Industrie- und
Spezialschmierstoffe**

*Industrial and
specialty lubricants*

PENNASOL PERFORMANCE TRUCK PREMIUM SAE 5W-30

PENNASOL PERFORMANCE TRUCK PREMIUM SAE 5W-30 is a fuel-saving UHPD engine oil for use in heavily loaded commercial vehicles all year round based on the latest additive technologies and high-quality base oils (HC & PAO). Specially designed for diesel engines under the most severe operating conditions. Developed for Euro IV & V engine technology with exhaust aftertreatment devices and diesel particulate filters (observe manufacturer's instructions).

PENNASOL PERFORMANCE TRUCK PREMIUM SAE 5W-30 ensures outstanding wear protection and a high lubricating film stability under all operating conditions.

Other advantages:

- Fuel Economy
- Excellent oxidation stability
- Excellent cold start attributes (SAE 5W-xx)
- Low evaporation tendency
- Suitable for oil change intervals up to more than 100,000 km (observe manufacturer's instructions)

ACEA-/API-specifications:

ACEA E7

ACEA E4

Meets/suitable for use:

(Meets the requirements of the OEM-Approval. An approval by name from the manufacturer is not present.)

Cummins CES 20077

Deutz DQC IV-10

Mack EO-N

MAN M 3277

MB 228.5

MTU Type 3

Scania LDF-3

Renault RLD-2

Voith retarder oil - Class B

Volvo VDS-3

Motorenöle

Motor oils

Getriebeöle

Gear oils

**Zweitaktöle und
Traktorenöle**

*Two-stroke oils and
tractor oils*

Hydrauliköle

Hydraulic oils

**Industrie- und
Spezialschmierstoffe**

*Industrial and
specialty lubricants*

			PENNASOL PERFROMANCE TRUCK PREMIUM SAE 5W-30
Parameter	Unit	Testing method	
Density 15°C	kg/m ³	DIN EN ISO 12185	857
Flash point COC	°C	DIN ISO 2592	> 200
Pour point	°C	DIN ISO 3016	-42
Viscosity 40°C	mm ² /s	DIN 51562-1	70.0
Viscosity 100°C	mm ² /s	DIN 51562-1	11.9
VI		DIN ISO 2909	166

04/2017

Version 5

The given data are typical data. Please observe operating prescriptions.

Available packaging:

	Bulk	965 Liter	208 Liter	60 Liter	20 Liter	4 * 5 Liter	12 * 1 Liter	Notes:
PENNASOL PERFROMANCE TRUCK PREMIUM SAE 5W-30	•	•	•	•	•			

1

¹ This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AVISTA OIL Group or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale.