



**Motorenöle**

*Motor oils*

**Getriebeöle**

*Gear oils*

**Zweitaktöle und  
Traktorenöle**

*Two-stroke oils and  
tractor oils*

**Hydrauliköle**

*Hydraulic oils*

**Industrie- und  
Spezialschmierstoffe**

*Industrial and  
specialty lubricants*

## **PENNASOL SUPER SPECIAL PLUS SAE 5W-20**

**PENNASOL SUPER SPECIAL PLUS SAE 5W-20** is fuel-efficient high-performance low -viscosity motor oil. Specially developed for the latest generation of Ford cars, for which the specification WSS-M2C948-B is prescribed, and for specific high-performance motors in Land Rover and Jaguar vehicles.

**PENNASOL SUPER SPECIAL PLUS SAE 5W-20** is suitable for use in gasoline and diesel engines, taking into account the operating instructions.

### **Other advantages:**

- High fuel efficiency (fuel economy)
- Low HTHS-Viscosity
- Excellent temperature-viscosity behavior
- Significant reduction of deposits
- Lubricating film stability even at high operating temperatures
- Excellent cold starting properties

### **ACEA/API-specifications:**

ACEA A1/B1

API SN

API CF (obsolete)

### **Meets/suitable for use:**

WSS-M2C948-B

**Motorenöle**
*Motor oils*
**Getriebeöle**
*Gear oils*
**Zweitaktöle und  
Traktorenöle**
*Two-stroke oils and  
tractor oils*
**Hydrauliköle**
*Hydraulic oils*
**Industrie- und  
Spezialschmierstoffe**
*Industrial and  
specialty lubricants*

			<b>PENNASOL SUPER SPECIAL PLUS</b>
Parameter	Unit	Testing method	<b>SAE 5W-20</b>
Density 15°C	kg/m <sup>3</sup>	DIN EN ISO 12185	852
Flash point COC	°C	DIN ISO 2592	min. 200
Pour point	°C	DIN ISO 3016	-45
Viscosity 40°C	mm <sup>2</sup> /s	DIN 51562-1	42.8
Viscosity 100°C	mm <sup>2</sup> /s	DIN 51562-1	8.0
VI		DIN ISO 2909	160

12/2017

Version 3

The given data are typical data. Please observe operating prescriptions.

**Available packaging:**

	Bulk	965 Liter	208 Liter	60 Liter	20 Liter	4 * 5 Liter	4 * 4 Liter	12 * 1 Liter	Bemerkung:
PENNASOL SUPER SPECIAL PLUS SAE 5W-20	•	•	•	•	•	•	•	•	

1

<sup>1</sup> This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AVISTA OIL Group or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale.